

SI 130TU

Data sheet



Experience Better Living.

Highly efficient brine-to-water heat pump for indoor installation.

Heat pump white textured (similar to RAL 9003). Heat pump for heating purposes with two performance levels for increased efficiency in partial load operation for indoor installation and integrated heat pump manager WPM Econ5Plus with standard display. Brine circulating pump 15 m delivery height at 18 m³/h, flange connection DN 65, installation length 340 mm, heat generator circuit pump 8 m delivery height at 14 m³/h, flange connection DN 65, installation length 340 mm. Use of load-variable tariffs (SG Ready) High coefficients of performance (COP) through electronic expansion valve and electronic pump control depending on the temperature spread in the brine and generator circuit. FWO function for more efficient domestic hot water preparation with increased domestic hot water temperatures and volumes of water to be drawn through optimised tank charging. Soft starter, flow and return sensors for the brine and heating circuit integrated. Dirt trap for brine circuit, external sensor (standard NTC-2), circulating pumps for brine and heat generator circuit in the scope of supply (observe the free compression). Sensor monitoring of the refrigeration circuit for a high degree of operational safety and integrated thermal energy metering (display of the calculated quantity of thermal energy for heating, domestic hot water and swimming pool water preparation). Brine package SZB must be ordered separately. Variable connection options for brine and heating connections on the back board of the casing. Bivalent or bivalent-renewable operating mode Distribution systems with unmixed and mixed heating circuits Access for service work from the front, no minimum clearance required on the sides, accessible from underneath with a lift truck. Universal design with two compressors for output regulation when operating at partial load, optional domestic hot water preparation and flexible expansion options for: A sound-optimised metal casing and the integrated solid-borne sound insulation with free-swinging compressor base plate make direct connection with the heating system possible.



Technical Data

Order reference	SI 130TU
Heating water flow rate acc. EN 1511	23.5
Heating water flow rate pressure drop according to EN 14511	13100
Heat source flow (min.)	27.3
Maximum electric power consumption	57.5
Nominal power consumption according to EN 14511 at B0/W35	30
Energy efficiency class with 35 °C flow temperature	A+++
Energy efficiency class with 55 °C flow temperature	A++
Seasonal space heating energy efficiency in average climate conditions (NT)	186
Seasonal room heating energy efficiency (high temperature)	138
Connection voltage	3/N/PE ~400 V, 50 Hz



Glen Dimplex Deutschland GmbH
Geschäftsbereich
Heating & Ventilation / Dimplex
Am Goldenen Feld 18
D-95326 Kulmbach

T + 49 9221 709 -101
F + 49 9221 709 -339
info@dimplex.de
www.dimplex.de

17.04.2024

SI 130TU

Data sheet



Experience Better Living.

Order reference	SI 130TU
Dimensions (W x H x D)**	1350 x 1900 x 840 mm
Weight	824 kg

* Heating and cooling capacity and coefficients of performance (COP/EER) in accordance with EN 14511

** Please note that additional space is required for pipe connection, operation and maintenance.

*** The fuse protection must be designed as an all-pole disconnecting device (common disconnection of all phases)!



Glen Dimplex Deutschland GmbH
Geschäftsbereich
Heating & Ventilation / Dimplex
Am Goldenen Feld 18
D-95326 Kulmbach

T + 49 9221 709 -101
F + 49 9221 709 -339
info@dimplex.de
www.dimplex.de

17.04.2024

WEEE-Reg-Nr. DE 26295273

SI 130TU

System accessories



Experience Better Living.

Description	Order-ref.	Article-number	Example Piece	Units	Price
Heat pump brine monobloc indoor					
Highly efficient brine-to-water heat pump for indoor installation.	SI 130TU	369960	1		
3-way reversing valve DN 50	DWV 50	374800	1		
Domestic hot water cylinder, 700 litres	WWSP 770	376730	1		
Accessories hydraulic					
3-way ball valve DN 50	DWK 50	364710	1		
Electronically controlled circulating pump with coupling relay	UPH 120-50F	379020	1		
Electronically controlled circulating pump with coupling relay	UPH 80-40F	371800	1		
Accessories for heating					
Heat pump heater heating/passive cooling, depth 16.5 cm	WPHK 1650100	381220	1		
Heat pump heater heating/passive cooling, depth 16.5 cm	WPHK 1650140	381230	1		
Heat pump heater heating/passive cooling, depth 16.5 cm	WPHK 1650180	381240	1		
Heat pump heater heating/passive cooling, depth 16.5 cm	WPHK 165080	381210	1		
Heat pump heater heating/passive cooling, depth 21.5 cm	WPHK 2150100	381250	1		
Heat pump heater heating/passive cooling, depth 21.5 cm	WPHK 2150140	381260	1		
Heat pump heater heating/passive cooling, depth 21.5 cm	WPHK 2150180	381270	1		
Heat pump heater vertical	WPHKV 1220053	381280	1		
Accessories domestic hot water					
Flow rate measurement for central domestic hot water heater	DFM 1988-500	377650	1		
Flow rate measurement for central domestic hot water heater	DFM 1988-700	379150	1		



Glen Dimplex Deutschland GmbH
Geschäftsbereich
Heating & Ventilation / Dimplex
Am Goldenen Feld 18
D-95326 Kulmbach

T + 49 9221 709 -101
F + 49 9221 709 -339
info@dimplex.de
www.dimplex.de

17.04.2024

WEEE-Reg-Nr. DE 26295273

SI 130TU

System accessories



Experience Better Living.

Description	Order-ref.	Article-number	Example Piece	Units	Price
3-way reversing valve DN 50	DWV 50	374800	1		
Electronically controlled circulating pump with coupling relay	UPH 80-40F	371800	1		
Pump unit DN 32 for direct connection of the domestic hot water cylinder	WPG 32	356040	1		
Domestic hot water cylinder (500l) with temperature sensor	WWSP 556	370080	1		
Domestic hot water cylinder, 700 litres	WWSP 770	376730	1		
Accessories solar					
400l solar cylinder for heat pump	WWSP 432 SOL	361080	1		
500 l solar cylinder for heat pump	WWSP 540 SOL	361090	1		
Accessories controls					
Remote control for WPM 2006/2007/EconPlus/R	AP PGD	356570	1		
Outside temperature sensor with casing	FG 3115	336620	1		
Expansion module WPM for a KNX/EIB connection	KNX WPM	376350	1		
Extension for a Modbus RTU connection	LWPM 410	339410	1		
Temperature sensor NTC-10 with metal sleeve	NTC-10M	363600	1		
Smart RTC+ - intelligent room temperature control	RTM Econ A	367210	1		
Smart RTC+ - intelligent room temperature control	RTM Econ U	367200	1		
Accessories for cooling					
3-way reversing valve DN 50	DWV 50	374800	1		
Room climate station for temperature and humidity measurement	RKS WPM	342220	1		
Dew point monitor	TPW WPM	350970	1		



Glen Dimplex Deutschland GmbH
Geschäftsbereich
Heating & Ventilation / Dimplex
Am Goldenen Feld 18
D-95326 Kulmbach

T + 49 9221 709 -101
F + 49 9221 709 -339
info@dimplex.de
www.dimplex.de

17.04.2024

WEEE-Reg-Nr. DE 26295273

SI 130TU

System accessories



Experience Better Living.

Description	Order-ref.	Article-number	Example Piece	Units	Price
Passive cooling controller	WPM Econ PK	360000	1		
Plate heat exchanger for SI 100	WTE 100	358460	1		
Plate heat exchanger for SI 130	WTE 130	358470	1		
Plate heat exchanger, copper-soldered	WTU 100	362390	1		
Plate heat exchanger, copper-soldered	WTU 130	362400	1		
Accessories heat source					
Connecting flange for heating and brine circuits	AF 80	351930	1		
Antifreeze for the brine circuit 200 l	AFN 824	324610	1		
Strap-on thermostat for temperature monitoring	RAT 060I	361470	1		
Brine package for SIH 90TU / SI 130TU	SZB 80F-50	368600	1		
Plate heat exchanger for SI 130	WTE 130	358470	1		

* Additional specific accessories available/required

Important notice

The combination of components and the specified quantities represent a non-binding example system that must be reviewed and, if necessary, adjusted individually.

The pumpsizing needs to be checked according to the system's pressure loss and the minimum heating water flow rate of the heat pump.



Glen Dimplex Deutschland GmbH
Geschäftsbereich
Heating & Ventilation / Dimplex
Am Goldenen Feld 18
D-95326 Kulmbach

T + 49 9221 709 -101
F + 49 9221 709 -339
info@dimplex.de
www.dimplex.de

17.04.2024

WEEE-Reg-Nr. DE 26295273